

TEMP 2S – IP68

Measure temperatures together in two places.



ALERT

- Provide warnings should thresholds be exceeded




MEASURE

- Monitor temperature changes



MONITOR

- Measure temperatures
- Identify temperature losses



BENEFITS

- Two remote probes
- Locally and remotely configurable
- Battery-powered stand-alone product
- Data logging for optimal autonomy
- Redundancy for better service continuity
- Timestamp (LoRaWAN®)
- Network test at startup (LoRaWAN®)
- KARE+ compatible



PRODUCT USES



Monitor the flow and return temperatures of the hydraulic circuits.



Monitor the temperature in a water circuit Sanitary Hot Water (DHW) to avoid the multiplication of bacteria called Legionella causing legionellosis.

TECHNICAL SPECIFICATIONS

- T° range remote probe:
Sensor: -55 + 155°C (+/-0,1) / Wire: -30 + 105°C
- Periodic mode with or without history
- Alarm on exceeding threshold
 - Data redundancy
 - Replaceable battery
- Dimensions: 132 x 62 x 34 mm
 - Weight: 185 g
 - Casing: IP68

- Configurable Life Screen
- Integrated fastening system: DIN rail, tube, wall, flange
- Zone: Sigfox: RC1 / LoRaWAN: EU863-870 / LoraWAN Class C
- Operating Temperature Range: -25 + 70°C
 - Standards: Directive 2014/53/EU (RED)
- Product error alert, configuration error, low battery

